

FILTRATION

ASTRALPOOL 

LAMINATED FILTER

Laminated filter made of fibreglass and polyester. Gray in colour, polypropylene base, new boltless lid, water drainage plug, flowmeter and side-mounted multiport valve. Maximum pressure of 2.5 kg/cm². Top filtration speed of 50 m³/h/m².



Aster Sand Filter, Side Mounted, without valve

ถังกรองทรายรุ่นแอสเตอร์ชนิดวาล์วข้าง

CODE	ITEM	SPECIFICATION					
		MULTIPORT	DIMENSIONS		FLOW RATE m ³ /hr	SILICA SAND (Kg)	RECOMMEND TO USE WITH PUMP
		Size	Width (mm)	Height (mm)			
19781-0100	Aster Filter Side/M D.500 (20") ถังกรองทรายรุ่นแอสเตอร์ ขนาด 20 นิ้ว	1-1/2"	500	770	9	4	0.5 HP
00499-0100	Aster Filter Side/M D.600 (24") ถังกรองทรายรุ่นแอสเตอร์ ขนาด 24 นิ้ว	1-1/2"	600	850	14	5	0.75 HP
00500-100	Aster Filter Side/M D.750 (30") ถังกรองทรายรุ่นแอสเตอร์ ขนาด 30 นิ้ว	2"	750	945	21	9	1 HP
08133-100	Aster Filter Side/M D.900 (36") ถังกรองทรายรุ่นแอสเตอร์ ขนาด 36 นิ้ว	2"	900	1050	32	12	2 HP
38928-0100	Aster Filter Side/M D.1200 (48") ถังกรองทรายรุ่นแอสเตอร์ ขนาด 48 นิ้ว	2-1/2"	1200	1070	52	34	3.5 HP