



## CLASSIC RP SERIES

### SALT WATER ELECTROLYSERS CHLORINE GENERATORS

- o Reverse polarity (reduced maintenance)
- o The reversing action de-scales the build-up of calcium and reduces electrode cleaning maintenance by 95%
- o Powered by transformer power supply
- o Salinity 5,000 ppm
- o Warranty: Residential application - 2 years, Commercial application - 1 year

RESIDENTIAL

| MODEL  | CHLORINE     | INPUT AC POWER CONSUMPTION | WATER FLOW      | DIMENSION (PACKAGED) | WEIGHT GROSS |
|--------|--------------|----------------------------|-----------------|----------------------|--------------|
|        | Grams / Hour | kW                         | Litres / Minute | L x W x H (cm)       | Kg           |
| RPMINI | 5            | 0.070                      | 200-400         | 37 x 31 x 22         | 11           |
| RP7    | 7            | 0.100                      | 200-400         | 39 x 19 x 30         | 5.5          |
| RP15   | 15           | 0.215                      | 200-400         | 37 x 31 x 22         | 11           |
| RP20   | 20           | 0.290                      | 200-400         | 37 x 31 x 22         | 11           |
| RP25   | 25           | 0.360                      | 200-400         | 37 x 31 x 22         | 11           |
| RP36   | 36           | 0.290                      | 200-400         | 37 x 31 x 22         | 11           |
| RP50   | 50           | 0.760                      | 200-400         | 43 x 33 x 27         | 27           |
| RP64   | 64           | 0.505                      | 200-400         | 43 x 33 x 27         | 27           |

#### OPTIONS (AVAILABLE TO AUSTRALIAN CUSTOMERS ONLY)

| PREFIX | DESCRIPTION                 | ADDITIONS AVAILABLE FOR |
|--------|-----------------------------|-------------------------|
| T      | Timer Option                | Mini/15/20/25/36/50/64  |
| QT     | Timer With Battery Back Up  | Mini/15/20/25/36/50/64  |
| L12    | Underwater Light Option 12V | Mini/15/20/25           |
| L24    | Underwater Light Option 24V | Mini/15/20/25           |
| L32    | Underwater Light Option 32V | Mini/15/20/25           |



NR: When ordering desirable model with options, simply add prefix to the model code. Example: AC25 TL12. Spare parts readily available including replacement cells. Recommended TDS level for AutoChlor operation: 5,000ppm\*