



“BSV” BS Series Residential Salt Chlorinators Made In Spain

COMPACT SALT WATER CHLORINATOR IN IP65 BOX WITH DIGITAL DISPLAY AND PRODUCTION FROM 10 TO 35 GRAMS FOR PRIVATE POOLS

- ✓ Lower electrical consumption
- ✓ Lower weight
- ✓ IP65 Waterproof Index
- ✓ Lower operating temperature.
- ✓ More compact, easily adaptable to any installation.
- ✓ Switch mode power supply improves importantly the unit performance.
- ✓ Longer durability of the electrolysis cell.
- ✓ Internal microprocessor control that determines the device operating hours



5K 5.000Hours **Low weight** **IP65** Box **Low Consumption**

| | N-Bsalt-10 | N-Bsalt-15 | N-Bsalt-20 | N-Bsalt-25 | N-Bsalt- 35 |
|---|------------------|------------|------------|------------|-------------|
| Tensión de alimentación Power Supply | 230Vac – 50/60Hz | | | | |
| Corriente máxima de la célula Max cell current | 10A | 15A | 20A | 25A | 35A |
| Producción gr/hora Gr/hour production | 10gr/h | 15gr/h | 20gr/h | 25gr/h | 35gr/h |
| Potencia máxima Max Power | 75W | 112,5W | 150W | 187,5W | 263W |
| Tensión máxima de la célula Max cell voltage | 7,5Vcc | | | | |
| Sal necesaria* Salt required* | 4gr/l | | | | |

Start up salt quantity is 5kgs per 1 m³ volume of water

| Code | Model | Gram/Hour | Recommended Pool Volume (m ³) at Turnover 8 Hours/Day | In & Outlet (Inches) |
|-------------|------------|-----------|--|-------------------------|
| 20900210120 | N-Bsalt-10 | 10 | 25 | 2 |
| 20900210125 | N-Bsalt-15 | 15 | 50 | 2 |
| 20900210130 | N-Bsalt-20 | 20 | 75 | 2 |
| 20900210135 | N-Bsalt-25 | 25 | 100 | 2 |
| 20900210140 | N-Bsalt-35 | 35 | 125 | 2 |