



POOL & SPA HEATER with Built-in flow switch

These compact and medium capacity pool and spa COAESE heaters feature a built-in flow switch to prevent operation when there is no water flow and allow operation at flow rate between 20GPM and 80GPM.

Features:

- ✓ The thermostat heating system applies to spa, swimming pool, adjusted according to the temperature required, heating, temperature, the temperature at 5 ~ 55 ° C adjustable, can be set within 1 to 15 hours . And when the water level is lower than the original set value, the system will automatically turn off the power, and the automatic climate control, safe and reliable.
- ✓ The digital control system keeps on monitoring the running status of every parts of the heater, and quickly reacts and displays corresponding hint message for any incident, so as to avoid any damage or malfunction happens.
- ✓ Automatic heating: thermostat will first reach the preset temperature, then stop working until the temperature dropped a few degrees, the thermostat automatically turns on

Specification:

Product Code	Power	Piping	Dimension (LxWxH)
CE-12411ST	11KW/380V/50HZ	1.5"	490x106x350mm.
CE-12415ST	15KW/380V/50HZ	1.5"	490x106x350mm.
CE-12418ST	18KW/380V/50HZ	1.5"	470x240x380mm.
CE-24PHS-2	24KW/380V/50HZ	2"	550x330x470mm.
CE-36PHS-2	36KW/380V/50HZ	2"	550x330x470mm.
CE-45PHS-2	45KW/380V/50HZ	2"	710x375x550mm.
CE-60PHS-2	60KW/380V/50HZ	2"	710x375x550mm.

