

DISINFECTION SYSTEMS



“EMAUX” NT-UV-T Series Nano Tech UV-C Systems With Timer

NANOTECH UV-C TIMER

Emaux Nano-Tech UVC Timer includes an integrated TIMER which is accurately monitors the operating hours of the UV-C lamp. You will be reminded when the lamp must be replaces

ADVANTAGE OF COMPRISING A TIMER

- User-friendly control pad with time clock and time meter display
- Integrated adjustable time meter for the UV-C lamp
- Digital indication when the lamp needs replacing



SAA



Note : "T" stands for Timer

Model	Max Flow Rate (m ³ /h)	Pool Vol (m ³)	Input Power	Maximum Pressure	Connections	Electric Ballast	Maximum Current (A)	UV Lamp lifetime (hr.)
NT-UV40-T	20	40	40W	3 bar	1.5"/50mm or 2"/63mm	120-240V AC	0.44(120V) 0.2(240V)	9,000
NT-UV75-T	25	75	75W	3 bar	1.5"/50mm or 2"/63mm	120-240V AC	0.82(120V) 0.38(240V)	9,000

Code	Model	Flowrate (m ³ /h)	Volume of Water (m ³)	Input Power (W)	Connection (Inches)
21000510025	NT-UV40-T	20	40	40	2"
21000510030	NT-UV75-T	25	75	75	2"