

DISINFECTION SYSTEMS



“EMAUX” SSC Series Semi-Commercial Salt Chlorinators

Salt Chlorinators, are an alternative means of sanitizing your pool with chlorine using the process of electrolysis. The electrolysis is achieved by passing the salt water solution through an electrolytic cell which converts sodium chloride (salt) into the water into chlorine gas which, when dissolved in water become sodium hypochlorite (liquid chlorine)

SAFE AND RESPECTING THE ENVIRONMENT, THIS TECHNOLOGY BRINGS YOU

- Relaxation : Your pool is automatically disinfected
- Safety : Reduction in chlorine storage and handling
- Comfort : Clean, safe and crystal-clear water
- Health and well-being : therapeutic, salt water does not irritate eyes and dry out skin

HIGHLIGHT FEATURES

- Self cleaning reverse polarity
- Quality Titanium cells
- Light Transformer models
- Cell life time 5000 – 8000 hours
- Maximum working pressure: 250kPa / 36psi / 2.5 bar




Technical Information


Model	Description	Salt Level (ppm)	Cell Output (gram/h)	Fiberglass Pool (L)	Concrete Pool (L)	Pool Light Voltage	Input Voltage /Freq	IP Rating	Weight (kg)
SSC15-E	Standard Version	4000	15	50,000	45,000	N/A	240V 50/60Hz	IPX4	6.5
SSC25-E			25	75,000	70,000				7.4
SSC50-E			45	120,000	110,000				9.7
SSC15-T	With Time Clock	4000	15	50,000	45,000	N/A	240V 50/60Hz	IPX4	6.6
SSC25-T			25	75,000	70,000				7.5
SSC50-T			45	120,000	110,000				9.8



แบบการติดตั้งเครื่องเกลือ "EMAUX" รุ่น SSC ที่ถูกต้อง



*ขนาดของถังเกลือ "EMAUX" สามารถระบุเป็นตัวเลข
 รหัสถังเกลือ
 ON — ใช้กับ TIMER ทั่วไป
 OFF — ทั่วไป
 AUTO — ใช้กับ TIMER ที่ติดตั้งในตัวเครื่อง



Standard Range of Salt Level in the Pool : 3500 – 4000 ppm

Commissioning Pool : Salt quantity is 3.5 - 4 Kg/m³

Maintenance Pool to maintain CL level at 1.5-2 ppm: Salt quantity is 3.5 – 4 Kg/m³

Code	Model	Type	Gram/Hour	Max. Pool Volume (m ³)		Power Consumption (Watts)
				Turnover Time 6 hr/day	Turnover Time 8 hr/day	
20900510080	SSC15-E	Standard Version (No Timer)	15	45	55	140
20900510085	SSC25-E		25	75	95	240
20900510090	SSC50-E		45	120	160	480
20900510005	SSC15-T	With Timer Clock	15	45	55	140
20900510010	SSC25-T		25	75	95	240
20900510015	SSC50-T		45	120	160	480