Perflex Extended-Cycle D.E. filters clean pools fast, removing particles as small as one micron the first time through. Its patented Flex-Tube™ design gives longer cycles between cleaning because the same D.E. filter powder is used over and over. Plus, Perflex cleans without backwashing, saving hundreds of gallons of treated pool water. An exceptional value as a replacement filter or for new pool installations. For sparkling, clean pools, step up to Perflex.

Applications

. In-ground pools of all types and sizes

Features

- Exclusive bump handle activates the mechanism causing the Flex-Tubes to instantly and uniformly clean themselves of dirt and filter powder
- Self-venting design automatically expels any air that may be present in the system
- Proven, patented Flex-Tube filter elements efficiently reuse the filter powder and dirt mixture forming a fresh filtering surface
- Combination pressure gauge and threaded inspection/ service port is easy to read and remove when filter needs cleaning
- Heavy-duty filter tank injection-molded of highstrength thermoplastic for dependable, corrosion-free performance
- Integral check valve prevents system backflow whenever pump is off

Performance Data

Model Number	Effective Filtration Area	Public Design Flow Rate*	Residential Design Flow Rate**	Turnover (In Gallons)		
				8 Hours	10 Hours	
EC65A	27 ft.2	54 GPM	:	25,920	40,200	
EC75A	40 ft.2	80 GPM		38,400	48,000	
EC65A			67 GPM	32,200	90,250	
EC75A			100 GPM	48,000	60,000	

NOTES: *Based on 2 GPM/ft.² (maximum allowable NSF rating).
**Based on 2.5 GPM/ft.² (maximum allowable NSF rating).







Perflex System

Perflex Extended-Cycle D.E. Filter Buying Guide

		2.1						
Model Number	1 ½" Drain Valve	1 ½" Pressure Gauge/ Inspection Port	Check Valve	D.E. Required	Dim Width	ensions Height	Ctn. Qty.	Ctn. Weight
EC65A	•	•	•	6 lbs.	21"	31*	1	44 lbs.
EC75A	٠	•	•	7 lbs.	21*	31"	1	45 lbs.
Model Number		Description					Ctn. Qty.	Ctn. Weight
Modular	System	Base Pak						
EC65BLP	Sys (les	1	15 lbs.					

NOTE: Order Super or Super II Pump, EC65A or EC75A basic filter and EC65BLP for a 3 component system.





EC65A, EC75A



EC652605X7 System III