

# Swim Pro TEXP/EXP



The Value Priced SwimPro EXP high rate sand filter range by Hayward is manufactured in the United States of rugged, durable colour-fast molded polymeric material to assure long life.

Each filter features a high efficiency top diffuser and innovative under-drain to assure balanced flow and maximize the filter's backwash performance. The top diffuser evenly distributes the unfiltered water across the entire sand media bed,

in a cascading umbrella like pattern. SwimPro's EXP included Vari-Flo multi-port control valve features seven positions to quickly and easily backwash the filter to clean the sand bed of dirt and debris.



Model Number	S170TEXP	S190TEXP	S230TEXP	S270TEXP	S311TEXP**
Valve	1 1/2" Vari-Flo	1 1/2" Vari-flo	1 1/2" Vari-flo	1 1/2" Vari-flo	2" Vari-flo
Effective Filtration Area	1.5 ft <sup>2</sup> / 0.14m <sup>2</sup>	1.8 ft <sup>2</sup> / 0.17 m <sup>2</sup>	2.7 ft <sup>2</sup> / 0.25 m <sup>2</sup>	3.7 ft <sup>2</sup> / 0.25 m <sup>2</sup>	4.95 ft <sup>2</sup> / 0.46 m <sup>2</sup>
Design Flow Rate*	30 gpm / 116 lpm	36 gpm / 140 lpm	54 gpm / 204 lpm	74 gpm / 280 lpm	99 gpm / 375 lpm
Sand Required	100 lbs. / 45 kg	175 lbs. / 79 kg	250 lbs. / 114kg	350 lbs. / 160 kg	350 lbs. / 160kg
Dimensions	17" W x 36 1/2" H (44 cm x 93 cm)	19" W x 36 1/2" H (49 cm x 93 cm)	23" W x 42 1/4" H (59 cm x 107 cm)	27" W x 42 1/4" H (69 cm x 107 cm)	31" W x 45 1/4" H (79 cm x 115 cm)

\*Based upon 20 GPM/Ft<sup>2</sup>, 814 LPM/m<sup>2</sup> (Maximum Allowable NSF Rating)

\*\* Spherical Tank

© 2017 Hayward Industries, Inc.



International Marketing Group  
2875 Pomona Blvd • Pomona CA 91768 USA