

SAUNA HEATER

Full Stainless Steel



INTERNAL & EXTERNAL CONTROL

Model	TOLO-A45-D	TOLO-A60-D	TOLO-A90-D
Power	4.5KW	6KW	9KW
Voltage / Phases	220V/1N or 380V/3N	220V/1N or 380V/3N	220V/1N or 380V/3N
Heating elements (Number * KW)	3*1.5KW	3*2KW	3*3KW
Control ways	Built in/ CON4/ Touch panel	Built in/ CON4/ Touch panel	Built in/ CON4/ Touch panel

3. Parameters And Dimensions

(Only apply to European style voltage and phase)

Model	Power	Voltage / Current	Sauna room m3	MIN. Distances to different walls (cm)				Size of wire	Stones Arrange
				side wall	Distance to shelf over 500mm above the floor	ceiling	floor		
TOLO-A30	3.0	215-240/13.6	2~4	5	5	110	18	3*2.5	12
TOLO-A45	4.5	215-240/20.5	3~6	8	8	110	18	3*6.0	18
		380-415/6.8						5*1.5	
TOLO-A60	6.0	215-240/27.3	5~9	10	15	110	18	3*10.0	18
		380-415/9.1						5*1.5	
TOLO-A90	9.0	215-240/40.9	9~13	13	20	110	18	3*10.0	20
		380-415/13.6						5*2.5	

Notes: Above room volume is subject to sauna room with heat preservation.

Table 1

