

SAUNA HEATER


Full Stainless Steel



INTERNAL & EXTERNAL CONTROL

Model	TOLO-C120	TOLO-C150	TOLO-C180	TOLO-C210	TOLO-C250	TOLO-C270
Power	12KW	15KW	18KW	21KW	25KW	27KW
Voltage / Phase	380V/3N	380V/3N	380V/3N	380V/3N	380V/3N	380V/3N
Heating elements (Number * KW)	6*2KW	3*2KW+ 3*3KW	9*2KW	6*2KW+ 3*3KW	7*3KW+2 *2KW	9*3KW
Control ways	CON4/ Touch panel	CON4/ Touch panel	CON4/ Touch panel	CON4/ Touch panel	CON4/ Touch panel	CON4/ Touch panel

3. Parameters And Dimensions

 (Only apply to European style voltage and phase)

Model	Power	Heating element	Sauna room volume m ³	Voltage	Current	Phase	Size of wire	Stones arrange
	KW	N*KW	Min~Max	V	A	N	N*mm ²	KG
TOLO-C105-A	10.5	3*1.5+3*2.0	9~15	380-415	16	3N	5*2.5	40~50
TOLO-C120-A	12.0	6*2.0	10~18	380-415	18	3N	5*4.0	40~50
TOLO-C150-A	15.0	3*2.0+3*3.0	13~23	380-415	23	3N	5*4.0	60~75
TOLO-C180-A	18.0	9*2.0	17~29	380-415	27	3N	5*6.0	85~100
TOLO-C210-A	21.0	6*2.0+3*3.0	20~33	380-415	32	3N	5*6.0	85~100
TOLO-C240-A	24.0	12*2	36~45	380-415	38	3N	5*10.0	85~100
TOLO-C270-A	27.0	9*3.0	38~50	380-415	41	3N	5*10.0	85~100

Notes: Above room volume is subject to sauna room with heat preservation.

Table 1